

| TYPE | Output kW | Amps A | Speed r/min | EFF. % | P.F. Cos | Tn/Tm | In/Im | Tst/Tn | Noise LwdB(A) | Weight Kg |
|-------------|-----------|--------|-------------|--------|----------|-------|-------|--------|---------------|-----------|
| IEC 100L-2 | 3 | 6.34 | 2860 | 83.6 | 0.87 | 2.2 | 7.5 | 2.3 | 76 | 30 |
| IEC 112M-2 | 4 | 8.2 | 2880 | 85.0 | 0.88 | 2.2 | 7.5 | 2.3 | 77 | 41 |
| IEC 132S1-2 | 5.5 | 11.1 | 2900 | 86.0 | 0.88 | 2.2 | 7.5 | 2.3 | 80 | 57.5 |
| IEC 132S2-2 | 7.5 | 14.9 | 2900 | 87.0 | 0.88 | 2.2 | 7.5 | 2.3 | 80 | 60.5 |
| IEC 160M1-2 | 11 | 21.2 | 2930 | 88.4 | 0.89 | 2.2 | 7.5 | 2.3 | 86 | 107 |
| IEC 160M2-2 | 15 | 28.6 | 2930 | 89.4 | 0.89 | 2.2 | 7.5 | 2.3 | 86 | 114 |
| IEC 160L-2 | 18.5 | 34.7 | 2930 | 90.0 | 0.90 | 2.2 | 7.5 | 2.3 | 86 | 133 |
| IEC 180M-2 | 22 | 41 | 2940 | 90.5 | 0.90 | 2.0 | 7.5 | 2.3 | 89 | 165 |
| IEC 200L1-2 | 30 | 55.4 | 2950 | 91.4 | 0.90 | 2.0 | 7.5 | 2.3 | 92 | 218 |
| IEC 200L2-2 | 37 | 67.9 | 2950 | 92.0 | 0.90 | 2.0 | 7.5 | 2.3 | 92 | 230 |
| IEC 225M-2 | 45 | 82.1 | 2960 | 92.5 | 0.90 | 2.0 | 7.5 | 2.3 | 92 | 290 |
| IEC 250M-2 | 55 | 100 | 2970 | 93.0 | 0.90 | 2.0 | 7.5 | 2.3 | 93 | 359 |
| IEC 280S-2 | 75 | 135 | 2975 | 93.6 | 0.90 | 2.0 | 7.0 | 2.3 | 94 | 475 |
| IEC 280M-2 | 90 | 160 | 2975 | 93.9 | 0.91 | 2.0 | 7.1 | 2.3 | 94 | 510 |
| IEC 315S-2 | 110 | 195 | 2976 | 94.0 | 0.91 | 1.8 | 7.1 | 2.2 | 96 | 875 |
| IEC 315M-2 | 132 | 233 | 2975 | 94.5 | 0.91 | 1.8 | 7.1 | 2.2 | 96 | 963 |
| IEC 315L1-2 | 160 | 282 | 2975 | 94.6 | 0.92 | 1.8 | 7.1 | 2.2 | 99 | 1010 |
| IEC 315L2-2 | 200 | 348 | 2975 | 94.8 | 0.92 | 1.8 | 7.1 | 2.2 | 99 | 1138 |
| IEC 355M-2 | 250 | 433 | 2980 | 95.3 | 0.92 | 1.6 | 7.1 | 2.2 | 103 | 1900 |
| IEC 355L-2 | 315 | 545 | 2980 | 95.6 | 0.92 | 1.6 | 7.1 | 2.2 | 103 | 2300 |
| | | | | | | | | | | |
| IEC 63M1-4 | 0.12 | 0.44 | 1310 | 57.0 | 0.72 | 2.1 | 4.4 | 2.2 | 52 | 4.5 |
| IEC 63M2-4 | 0.18 | 0.62 | 1310 | 60.0 | 0.73 | 2.1 | 4.4 | 2.2 | 52 | 4.7 |
| IEC 71M1-4 | 0.25 | 0.79 | 1345 | 65.0 | 0.74 | 2.1 | 5.2 | 2.2 | 55 | 6 |
| IEC 71M2-4 | 0.37 | 1.12 | 1340 | 67.0 | 0.75 | 2.1 | 5.2 | 2.2 | 55 | 6.3 |
| IEC 80M1-4 | 0.55 | 1.57 | 1390 | 71.0 | 0.75 | 2.4 | 5.2 | 2.3 | 58 | 15 |
| IEC 80M2-4 | 0.75 | 2.05 | 1380 | 73.0 | 0.76 | 2.3 | 6.0 | 2.3 | 58 | 15.5 |
| IEC 90S-4 | 1.1 | 2.85 | 1390 | 76.2 | 0.77 | 2.3 | 6.0 | 2.3 | 61 | 19 |
| IEC 90L-4 | 1.5 | 3.72 | 1400 | 78.5 | 0.78 | 2.3 | 6.0 | 2.3 | 61 | 23 |
| IEC 100L1-4 | 2.2 | 5.09 | 1420 | 80.0 | 0.81 | 2.3 | 7.0 | 2.3 | 64 | 29 |
| IEC 100L2-4 | 3 | 6.78 | 1410 | 82.6 | 0.82 | 2.3 | 7.0 | 2.3 | 64 | 31 |
| IEC 112M-4 | 4 | 8.8 | 1435 | 84.2 | 0.82 | 2.3 | 7.0 | 2.3 | 65 | 42 |
| IEC 132S-4 | 5.5 | 11.7 | 1440 | 85.7 | 0.83 | 2.3 | 7.0 | 2.3 | 71 | 63.5 |
| IEC 132M-4 | 7.5 | 15.6 | 1450 | 87.0 | 0.84 | 2.3 | 7.0 | 2.3 | 71 | 72 |
| IEC 160M-4 | 11 | 22.5 | 1460 | 88.4 | 0.84 | 2.2 | 7.0 | 2.3 | 75 | 110 |
| IEC 160L-4 | 15 | 30 | 1460 | 89.4 | 0.85 | 2.2 | 7.5 | 2.3 | 75 | 129 |
| IEC 180M-4 | 18.5 | 36.3 | 1470 | 90.5 | 0.86 | 2.2 | 7.5 | 2.3 | 76 | 160 |
| IEC 180L-4 | 22 | 43.2 | 1470 | 91.0 | 0.86 | 2.2 | 7.5 | 2.3 | 76 | 178 |
| IEC 200L-4 | 30 | 57.6 | 1470 | 92.0 | 0.86 | 2.2 | 7.2 | 2.3 | 79 | 228 |
| IEC 225S-4 | 37 | 70.2 | 1475 | 92.5 | 0.87 | 2.2 | 7.2 | 2.3 | 81 | 288 |
| IEC 225M-4 | 45 | 84.9 | 1475 | 92.8 | 0.87 | 2.2 | 7.2 | 2.3 | 81 | 313 |
| IEC 250M-4 | 55 | 103 | 1480 | 93.0 | 0.87 | 2.2 | 7.2 | 2.3 | 83 | 376 |