

TYPE	Output kW	Amps A	Speed r/min	EFF. %	P.F. Cos	Tn/Tm	In/Im	Tst/Tn	Noise LwdB(A)	Weight kg
IEC 90L-8	0.55	2.17	680	63.0	0.61	1.8	4.0	2.0	56	23
IEC 100L1-8	0.75	2.43	680	71.0	0.67	1.8	4.0	2.0	59	29
IEC 100L2-8	1.1	3.36	680	73.0	0.69	1.8	5.0	2.0	59	31
IEC 112M-8	1.5	4.4	690	75.0	0.70	1.8	5.0	2.0	61	41
IEC 132S-8	2.2	6.0	710	79.0	0.71	1.8	6.0	2.0	64	61
IEC 132M-8	3.0	7.8	710	80.0	0.73	1.8	6.0	2.0	64	74
IEC 160M1-8	4.0	10.3	720	81.0	0.73	1.9	6.0	2.0	68	95
IEC 160M2-8	5.5	13.6	720	83.0	0.74	1.9	6.0	2.0	68	107
IEC 160L-8	7.5	17.8	720	85.5	0.75	1.9	6.0	2.0	68	128
IEC 180L-8	11	25.5	730	87.5	0.75	2.0	6.5	2.0	70	169
IEC 200L-8	15	34.1	730	88.0	0.76	2.0	6.6	2.0	73	236
IEC 225S-8	18.5	41.1	730	90.0	0.76	1.9	6.6	2.0	73	274
IEC 225M-8	22	48.9	730	90.5	0.78	1.9	6.6	2.0	73	290
IEC 250M-8	30	63	735	91.0	0.79	1.9	6.5	2.0	75	370
IEC 280S-8	37	78	740	91.5	0.79	1.9	6.6	2.0	76	488
IEC 280M-8	45	94	740	92.0	0.79	1.9	6.6	2.0	79	563
IEC 315S-8	55	111	735	92.8	0.81	1.8	6.6	2.0	82	852
IEC 315M-8	75	150	735	93.5	0.81	1.8	6.6	2.0	82	933
IEC 315L1-8	90	178	735	93.8	0.82	1.8	6.6	2.0	82	1027
IEC 315L2-8	110	217	735	94.0	0.82	1.8	6.4	2.0	82	1117
IEC 355M1-8	132	261	740	93.7	0.82	1.8	6.4	2.0	90	2000
IEC 355M2-8	160	315	740	94.2	0.82	1.8	6.4	2.0	90	2150
IEC 355L-8	200	387	740	94.5	0.83	1.8	6.4	2.0	90	2250
IEC 315S-10	45	100	590	91.5	0.75	1.5	6.2	2.0	82	818
IEC 315M-10	55	121	590	92	0.75	1.5	6.2	2.0	82	903
IEC 315L1-10	75	162	590	92.5	0.76	1.5	6.2	2.0	82	1007
IEC 315L2-10	90	191	590	93	0.77	1.5	6.2	2.0	82	1100
IEC 355M1-10	110	230	590	93.2	0.78	1.3	6.0	2.0	90	1800
IEC 355M2-10	132	275	590	93.5	0.78	1.3	6.0	2.0	90	2000
IEC 355L-10	160	334	590	93.5	0.78	1.3	6.0	2.0	90	2500